

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: V2 Basalt/Fiberglass Fabrics

Other names: Multiaxial fabric, stitched fabric, non-crimp fabric, knitted fabric

Synonyms: V, VI, VIX, VT, VTX, VX, VXV

Recommended use: For use in composite or other industrial applications as a reinforcement

in combination with other materials.

Restrictions of Use: None

Manufacturer's Name: V2 Composites, Inc.

Address: 770 Lee Road 191 Auburn, Alabama 36830

Telephone: 334-502-3000

Emergency phone number 334-502-3000

Facsimile: 334-502-3088

Website: <u>www.v2composites.com</u>

SECTION 2 - HAZARDS IDENTIFICATION

OSHA/HCS status: While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and

available for employees and other users of this product.

Classification of the

substance or mixture: Not classified.

GHS label elements

Signal word: No signal word.

Hazard Statements: No known significant effects or critical hazards.

Precautionary Statements

Prevention: Not applicable.
Response: Not applicable.
Storage: Not applicable.
Disposal: Not applicable.

Supplemental label elements: Emits toxic fumes when heated.

Hazards not otherwise classified: None known.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name: Fiber Glass (E-type, continuous filament, non-respirable)

Basalt Fiber Polyester Veil

Polyester Yarn (POY, Polyethylene Terephthalate Partially Oriented)

Sizing (Organic Surface Binder)

Common Name and Synonyms: Fiber Glass: E-Glass, glass mat, multiaxial, stitched, non-crimp, knitted fabric

Basalt Fiber: Continuous Basalt Roving

Polyester Veil: Nonwoven, CFM, CSM, Flow Media

Polyester Yarn: V-Lock

Sizing: Binder

Mixtures:

Ingredient Name	% by Volume	CAS number
Fiber Glass	1-100%	65997-17-3
Basalt	1-100%	65997-17-3
Polyester Veil	0-25%	25038-59-9
Polyester Yarn	0-5%	25038-59-9
Sizing	0-5%	Not available



SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Any concentration shown as a range is to protect confidentially or is due to batch variation.

There are no additional ingredients, present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4 - FIRST AID MEASURES

Relevant routes of exposure

Inhalation: Inhalation is unlikely to occur unless the basalt or fiberglass is being mechanically ground or

sanded from continuous fibers in to dust. If irritation to respiratory tract occurs and persists

remove from area to fresh air. If symptoms persist, contact a poison control center,

emergency room, or a physician for treatment information.

Eye Contact: Remove contact lens and pour a gentle stream of warm water through the affected area

for 15 minutes. Do not rub or scratch eyes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

Skin Contact: Remove contaminated clothing and shoes. Run cold water over the affected ares for 15

minutes with mild soap, Do not use warm water. DO NOT rub or scratch affected area.

If irritation persists or glass fiber becomes embedded, seek medical attention.

Ingestion: Gently wipe or rinse the inside of the mouth with water. Sips of water can be given. Never

give anything by mouth to an unconscious person. Contact a poison control center,

emergency room, or physician for treatment information.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, foam, carbon dioxide and water fog.

Unsuitable Extinguishing Media: None known

Specific Hazards from the chemical

during a fire:

Material is not an electrical conductor and may accumulate a static charge.

Hazardous thermal decomposition

products:

Fiberglass will not burn, but smoking of the product may occur at approximately 400-500 deg.F (approximately 200-260 deg C) due to decomposition of the surface binder. Surface binders

may decompose in a fire situation and release carbon monoxide, carbon dioxide and water. Additionally, there are many chemicals that can evolve during any partial decomposition of chemical products. The amounts or identities cannot be predicted and can differ in each case.

Special protective equipment for fire-

fighters:

Fiberglass and basalt will not support combustion, but in a sustained fire, proper protection such as a self-contained breathing apparatus (SCBA) and full firefighting gear should be worn.



SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection equipment recommended in Section 8. **Environmental Precautions:** No special precautions are needed in case of a release or spill.

Containment: This material will settle out of the air. Prevent from spreading by covering.

Methods for clean up: Use an industrial vacuum cleaner with a high efficiency filter to clean up dust

Sweep or gather up material and place in proper container for disposal or recovery.

Use vacuuming or wet sweeping methods instead of dry sweeping.

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid dust formation, do not breath dust and wear personal protective equipment.

Advice on general hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled,

stored and processed. Workers should wash hands and face before eating drinking

and smoking. Remove contaminated clothing and protective equipment before entering eating

areas. See also Section 8 for additional information on hygiene measures.

Storage: Store at or below 25 degrees Celsius (77*F) and relative humidity about 65% for optimum

performance. Material is not an electrical conductor, and may accumulate static charge.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

8-hour Time Weighted Average (TWA); 15-minute Short-Term Exposure Limit (STEL)

OSHA: 15mg/m3 TWA 5mg/m3 TWA (respirable dust) 15mg/m3 TWA (total dust)

ACGIH TLV: TWA: 1f/cc Form: Continuous filament glass fibers

TWA: 5mg/m3, Inhalable form: Continuous filament glass fibers

TWA: 3mg/m3 Form: Respirable TWA: 10mg/m3 Form: Total dust

ACGIH TLV US 6/13: TWA: 5mg/m3 8 hours, Form: Inhalable fraction

TWA: 1f/cc 8 hours. Form: Respirable fibers: length greater than 5uM; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450x magnification(4-mm objective) phase contrast

illumination.

Engineering Controls: Use local exhaust or general room/dilution ventilation sufficient to maintain employee

exposure below permissible exposure limits.

Eye Protection: Standard safety glasses with side shields.

Skin Protection: Protective gloves and long sleeved shirt and long pants.

Hygiene Measures: Wash hands before and after breaks. Wear clean, body-covering clothing. Good personal hygiene and the use

of barrier creams, caps, protective gloves, cotton coveralls or long sleeved loose fitting clothing will maximize comfort. Vacuum equipment may be used to remove fibers from clothes. Work clothing should be laundered

separately form other clothing before reuse.

Respiratory Protection: If dust is generated and ventilation is inadequate, use respirator that will protect against dust/mist.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product

and the safe working limits of the selected respirator.



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid

Appearance/Color: White or off white for fiberglass, basalt is dark brown or gold

Odorless

Odor Threshold: NA
Vapor Pressure: NA
Vapor Density: NA
pH: NA

Relative Density: 2.6-2.7 g/cc Solubility (wt.% in water): Insoluble

Freezing/Melting Point: >~1400°F (800°C) for fiberglass/ ~1050°C for basalt(softening point)

Boiling Point: NA Flash Point: NA **Evaporation Rate:** NA Flammability: NA **Explosive limits:** NA Partition coefficient: n-octanol/water NA **Auto Ignition Temp:** NA **Decomposition Temp:** NA

Viscosity:

Volume % Volatile:

Percent Solid

NA

100

SECTION 10 - STABILITY AND REACTIVITY

Reactivity:No specific test data related to reactivity available for this product or its ingredients.

Chemical Stability: This product is stable.

Possible hazardous reactions: Hazardous reactions will not occur under normal conditions.

Conditions to avoid: Humidity >65% When exposed to high temperatures may produce hazardous decomposition

products. Refer to protective measures listed in sections 7 and 8.

Incompatible materials: None known.

Hazardous decomposition products: Fiberglass products may release small amouts of acetic acid and other organic materials

at elevated temperatures.



SECTION 11 - TOXICOLOGICAL INFORMATION

Acute toxicity: No known significant effects or critical hazards.

Irritation/Corrosion:

Skin: No known significant effects or critical hazards. Eves: No known significant effects or critical hazards. No known significant effects or critical hazards. Respiratory:

Sensitization:

Skin: No known significant effects or critical hazards. Respiratory: No known significant effects or critical hazards. **Mutagenicity:** No known significant effects or critical hazards. **Carcinogenicity:** No known significant effects or critical hazards.

Classification

Product/ingredient name	OSHA	IARC	NTP
glass, oxide, chemicals	-	3	-

Reproductive toxicity: No known significant effects or critical hazards.

Teratogenicity:

Specific target organ toxicity

(single exposure):

Specific target organ toxicity

(repeated exposure):

Target Organs:

Contains material which may cause damage to the following organs: upper respiratory tract,

No known significant effects or critical hazards.

skin, and eyes.

Not available.

Not available.

Aspiration hazard: Not available.

Likely routes of exposure

Potential acute health effects

Eye Contact: Dusts from this product may cause temporary mechanical irritation. Inhalation: Dusts from this product may cause temporary mechanical irritation.

Skin Contact: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory

tract.

Although ingestion of this product is not likely to occur in industrial applications, accidental Ingestion:

ingestion may cause illness or irritation of the mouth and gastrointestinal tract.

Over-exposure signs/symptoms

Eve Contact: No specific data. Inhalation: No specific data. Skin Contact: No specific data. Ingestion: No specific data.



Delayed and immediate effects and chronic effects of short and long term exposure

SUMMARY: There are no known health effects from the long term use or contact, with **nonrespirable** continuous filament fibers. As manufactured, the glass and basalt fibers in this product are nonrespirable. Nonrespirable fibers cannot reach the deep lung because they have a diameter of greater than 3.5 micrometers. Fibers of this diameter cannot penetrate the narrow, bending passages of the human respiratory tract to reach the lower regions of the lung and thus, have no possibility of causing serious pulmonary damage. Instead, they deposit on the surface of the upper respiratory tract, nose, or pharynx. These fibers are then cleared through normal physiological mechanisms.

Chopped, crushed, or severely mechanically processed fiber glass may contain a very small amount of respirable fibers that could reach the deep lung. The measured airborne concentration of these respirable fibers in areas where severe processing of fiberglass occurred has been shown to be extremely low and well below the TLV. Repeated or prolonged exposure to respirable glass fibers may cause fibrosis, lung cancer and mesolthelioma. Fiberglass and basalt in the form supplied, does not contain respirable fibers.

Animal Study: In 2000, the Institute of Occupational Medicine (IOM) in Scotland published the results of a long term inhalation study in animals exposed to special application E-glass continuous filament respirable fibers. Animals were exposed to a very high concentration of these respirable fibers (1022 fibers/cc for 5 hours/day, 7 days/week for 52 weeks). Exposure to these microfibers resulted in the development of fibrosis, lung cancer and mesothelioma.

Epidemiology Studies: Two major studies in the US (performed by the University of Pittsburgh) and Europe (performed by the International Agency for Research on Cancer) showed no increase in lung cancer or respiratory disease among people working in fiber glass production facilities. An additional smaller study performed in Canada also did not show an association between exposure of workers to fiber glass and respiratory cancer.

Short term exposure

Potential immediate effects: No known significant effects or critical hazards. **Potential delayed effects:** No known significant effects or critical hazards.

Long term exposure

Potential immediate effects: No known significant effects or critical hazards. **Potential delayed effects:** No known significant effects or critical hazards.

Potential Chronic health effects

General:

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Mutagenicity:
No known significant effects or critical hazards.

Teratogenicity:
No known significant effects or critical hazards.

Delevopmental effects:
No known significant effects or critical hazards.

No known significant effects or critical hazards.

Fertility effects:
No known significant effects or critical hazards.

Acute toxicity estimates: Not available.

SECTION 12 - ECOLOGICAL INFORMATION

Toxicity: Not available
Persistence and degradability Not available
Bioaccumulative Potential Not available

Mobility in soil

Soil/water partition coefficient(Koc): Not available



SECTION 13 - DISPOSABLE CONSIDERATIONS

Disposal Method:

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees, as well as Section 6: ACCIDENTAL RELEASE MEASURES.

All components are listed or exempted.

No products were found

SECTION 14 - TRANSPORT REGULATIONS

Transport Classification:
Special Precautions for user:

This product is not classified as a hazardous chemical and not regulated for transport. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15 - REGULATORY INFORMATION

USA TSCA: All components are listed or exempted. **EUROPE REACH:** All components are listed or exempted. **DSL: CANADA** All components are listed or exempted. **AUSTRALIA AICS:** All components are listed or exempted. All components are listed or exempted. **NEW ZEALAND(NZIoC): KOREA KECI:** All components are listed or exempted. **JAPAN MITI (ENCS):** All components are listed or exempted. **PHILIPPINES PICCS:** All components are listed or exempted.

UNITED STATES SARA 302/304:

CHINA IECSC:

SARA 304 RQ Not applicable

Composition/information on ingredients

SARA 311/312:

Classification: Not applicable

Composition/information on ingredients
No products were found

State of California

The Proposition 65 List: No products were found

SECTION 16 - OTHER INFORMATION

HMIS HEALTH HAZARD: 1
HMIS FLAMMABILITY HAZARD 0
HMIS REACTIVITY 0

The customer is responsible for determining the PPE code for this material.

SDS ISSUE DATE: 8/28/2018

SDS VERSION NUMBER: 1

SDS FORMAT: (HCS)(29 CFR 1910.1200(g))

SDS REVISION NOTES:

SDS AUTHOR: DLM

Disclaimer: V2 Composites does not manufacture the components in the product. Component safety data sheets are available upon request. The SDS originates from the component SDS. Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.